

MR-212,MR-210,MR-112

Lower Midrange Arrays

The EAW MR series of direct radiating lower midrange arrays are intended for concert sound, theater reinforcement, or any near field high level playback application requiring natural low distortion response at high sound pressure levels. The use of an MR series in three and four way systems enables improved vocal definition and clarity.

Cabinet construction is of multi-ply cross laminated baltic birch. Standard features include perforated steel grills, recessed handles, roadie corners, and quick-mounting speaker hardware.

The MR-212 will house two 12" drivers. The MR-210 requires two 10" drivers. Both units are horizontally splayed for better coverage at higher frequencies. The MR-112 is intended for use with a single 12 inch driver.



	MR-212	MR-210	MR-112
Drivers Required:	Two 12"	Two 10"	One 12"
Internal Volume			
Cubic Feet:	3.9	3.1	1.7
Litres:	110	88	49
Recommended Drivers:	ATC PA-75-PDM	PAS LR-1080	ATC PA-75-PDM
Sensitivity (1W at 1m):	102 dB	99 dB	99 dB
Power Handling:	300 W RMS	200 W RMS	150 W RMS
Frequency Response:	200-1600 Hz	300-1500 Hz	250-1600 Hz
Dimensions (HxWxD):	14.5"x29.75"x19.75"	11.25"x29.75"x19.75"	20.5"x16"x11.75"