

	CSC923	CSC923X	CSC723	CSC723X
System Configuration	Triamplified 3-way	Bi-amplified 3-way	Triamplified 3-way	Bi-amplified 3-way
Components	4x 15-in vented, 1x 10-in horn-loaded, 2-in compression driver on asymmetrical horn	4x 15-in vented, 1x 10-in horn-loaded, 2-in compression driver on asymmetrical horn	2x 15-in vented, 1x 10-in horn-loaded, 2-in compression driver on asymmetrical horn	2x 15-in vented, 1x 10-in horn-loaded, 2-in compression driver on asymmetrical horn
Frequency Response (± 3 dB)	35 Hz - 18 kHz	SMPT/ISO 2969 "X" curve 35 Hz - 18 kHz	35 Hz - 18 kHz	SMPT/ISO 2969 "X" curve 35 Hz - 18 kHz
SENSITIVITY (1W/1M)				
<i>Passive/Bi- or Triamped LF</i>	103 dB SPL	103 dB SPL	101 dB SPL	101 dB SPL
<i>Triamped MF</i>	108 dB SPL	-	108 dB SPL	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	114 dB SPL	108 dB SPL	114 dB SPL	108 dB SPL
POWER HANDLING (AES)				
<i>Passive/Bi- or Triamped LF</i>	2000 Watts	2000 Watts	1000 Watts	1000 Watts
<i>Triamped MF</i>	350 Watts	-	350 Watts	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	120 Watts	350 Watts	120 Watts	350 Watts
PEAK OUTPUT (1M)				
<i>Passive/Bi- or Triamped LF</i>	142.0 dB SPL	142.0 dB SPL	136.0 dB SPL	136.0 dB SPL
<i>Triamped MF</i>	139.4 dB SPL	-	139.4 dB SPL	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	140.8 dB SPL	139.4 dB SPL	140.8 dB SPL	139.4 dB SPL
IMPEDANCE (Nominal)				
<i>Passive/Bi- or Triamped LF</i>	2x 4 Ohms	2x 4 Ohms	4 Ohms	4 Ohms
<i>Triamped MF</i>	8 Ohms	-	8 Ohms	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	12 Ohms	8 Ohms	12 Ohms	8 Ohms
Coverage ($h^\circ \times v^\circ$)	80-90(asymmetrical)x50	80-90(asymmetrical)x50	80-90(asymmetrical)x50	80-90(asymmetrical)x50
Recommended Crossover	200/1000 Hz	200 Hz	250/1000 Hz	250 Hz
DIMENSIONS (H X W X D)				
<i>inches</i>	90.5 x 32.0 x 22.5	90.5 x 32.0 x 22.5	65.5 x 32.0 x 22.5	65.5 x 32.0 x 22.5
<i>millimeters</i>	2299 x 813 x 571	2299 x 813 x 571	1664 x 813 x 571	1664 x 813 x 571
WEIGHTS (Net/Shipping)				
<i>pounds</i>	309.0/329.0	309.0/329.0	204.0/224.0	204.0/224.0
<i>kilograms</i>	140.16/149.04	140.16/149.04	92.53/101.47	92.53/101.47



CB523M	CB523MX	CB423M	CB423MX	CB153	CB153X
Triamplified 3-way	Biamplified 3-way	Triamplified 3-way	Biamplified 3-way	Biamplified 3-way	Passive 3-way
2x 15-in vented, 10-in horn-loaded, 1.4-in compression driver on CD horn	2x 15-in vented, 10-in horn-loaded, 1.4-in compression driver on CD horn	1x 15-in vented, 10-in horn-loaded, 1.4-in compression driver on CD horn	1x 15-in vented, 10-in horn-loaded, 1.4-in compression driver on CD horn	1x 15-in vented, 8-in vented, 1-in compression driver on WGP	1x 15-in vented, 8-in vented, 1-in compression driver on WGP
42 Hz - 19 kHz	42 Hz - 19 kHz	42 Hz - 19 kHz	42 Hz - 19 kHz	40 Hz - 18 kHz	40 Hz - 18 kHz
101 dB SPL	101 dB SPL	98 dB SPL	98 dB SPL	98 dB SPL	98 dB SPL
108 dB SPL	-	108 dB SPL	-	-	-
112 dB SPL	104 dB SPL	112 dB SPL	104 dB SPL	98 dB SPL	-
1000 Watts	1000 Watts	500 Watts	500 Watts	500 Watts	320 Watts
325 Watts	-	325 Watts	-	-	-
200 Watts	350 Watts	200 Watts	350 Watts	320 Watts	-
137.0 dB SPL	137.0 dB SPL	131.0 dB SPL	131.0 dB SPL	131.0 dB SPL	129.0 dB SPL
139.1 dB SPL	-	139.1 dB SPL	-	-	-
141.0 dB SPL	135.4 dB SPL	141.0 dB SPL	135.4 dB SPL	127.0 dB SPL	-
4 Ohms	4 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
8 Ohms	-	8 Ohms	-	-	-
12 Ohms	8 Ohms	12 Ohms	8 Ohms	8 Ohms	-
90x45	90x45	90x45	90x45	90x90	90x90
350/1300 Hz	350 Hz	350/1475 Hz	350 Hz	350 Hz	-
69.41 x 24.80 x 17.75 1763 x 630 x 451	69.41 x 24.80 x 17.75 1763 x 630 x 451	51.66 x 24.83 x 22.20 1312 x 631 x 564	51.66 x 24.83 x 22.20 1312 x 631 x 564	50.60 x 36.13 x 13.90 1285 x 918 x 353	50.60 x 36.13 x 13.90 1285 x 918 x 353
215.0/230.0 97.5/104.3	215.0/230.0 97.5/104.3	150.0/165.0 68.1/74.9	150.0/165.0 68.1/74.9	105.0/115.0 47.8/52.3	105.0/115.0 47.8/52.3



Sound is Half the Picture