

	CB2592	CB2591	CB2591X	CB259	CB259X
System Configuration	Bi-amplified 2-way	Bi-amplified 2-way	Passive 2-way	Bi-amplified 2-way	Passive 2-way
Components	4x 15-in vented, 2-in compression driver on CD horn	2x 15-in vented, 2-in compression driver on CD horn	2x 15-in vented, 2-in compression driver on CD horn	2x 15-in vented, 2-in compression driver on CD horn	2x 15-in vented, 2-in compression driver on CD horn
Frequency Response (± 3 dB)	42 Hz - 18 kHz	42 Hz - 16 kHz	42 Hz - 18 kHz	42 Hz - 17 kHz	42 Hz - 17 kHz
<hr/>					
SENSITIVITY (1W/1M)					
<i>Passive/Bi- or Triamped LF</i>	103 dB SPL	101 dB SPL	100 dB SPL	101 dB SPL	101 dB SPL
<i>Triamped MF</i>	-	-	-	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	111 dB SPL	111 dB SPL	-	111 dB SPL	-
POWER HANDLING (AES)					
<i>Passive/Bi- or Triamped LF</i>	2000 Watts	1000 Watts	500 Watts	1000 Watts	500 Watts
<i>Triamped MF</i>	-	-	-	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	100 Watts	100 Watts	-	100 Watts	-
PEAK OUTPUT (1M)					
<i>Passive/Bi- or Triamped LF</i>	142.0 dB SPL	137.0 dB SPL	133.0 dB SPL	137.0 dB SPL	134.0 dB SPL
<i>Triamped MF</i>	-	-	-	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	137.0 dB SPL	137.0 dB SPL	-	137.0 dB SPL	-
IMPEDANCE (Nominal)					
<i>Passive/Bi- or Triamped LF</i>	2x 4 Ohms	4 Ohms	4 Ohms	4 Ohms	4 Ohms
<i>Triamped MF</i>	-	-	-	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	12 Ohms	12 Ohms	-	12 Ohms	-
Coverage ($h^\circ \times v^\circ$)	90x40	90x40	90x40	90x40	90x40
Recommended Crossover	500 Hz	500 Hz	-	800 Hz	-
<hr/>					
DIMENSIONS (H X W X D)					
<i>inches</i>	112.44 x 37.63 x 33.22	77.75 x 29.00 x 34.19	77.75 x 29.00 x 34.19	54.19 x 24.44 x 17.75	54.19 x 24.44 x 17.75
<i>millimeters</i>	2856 x 956 x 844	1975 x 737 x 868	1975 x 737 x 868	1376 x 621 x 397	1376 x 621 x 397
<hr/>					
WEIGHTS (Net/Shipping)					
<i>pounds</i>	343.5/391.5	203.5/237.5	203.5/237.5	160.5/177.5	160.5/177.5
<i>kilograms</i>	156.3/178.1	92.6/108.1	92.6/108.1	73.0/80.8	73.0/80.8



	CB152	CB152X
System Configuration	Bi-amplified 2-way	Passive 2-way
Components	15-in vented, 1.4-in compression driver on CD horn	15-in vented, 1.4-in compression driver on CD horn
Frequency Response (± 3 dB)	45 Hz - 17 kHz	40 Hz - 18 kHz
<hr/>		
SENSITIVITY (1W/1M)		
<i>Passive/Bi- or Triamped LF</i>	98 dB SPL	98 dB SPL
<i>Triamped MF</i>	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	110 dB SPL	-
POWER HANDLING (AES)		
<i>Passive/Bi- or Triamped LF</i>	500 Watts	500 Watts
<i>Triamped MF</i>	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	150 Watts	-
PEAK OUTPUT (1M)		
<i>Passive/Bi- or Triamped LF</i>	131.0 dB SPL	131.0 dB SPL
<i>Triamped MF</i>	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	137.0 dB SPL	-
IMPEDANCE (Nominal)		
<i>Passive/Bi- or Triamped LF</i>	8 Ohms	8 Ohms
<i>Triamped MF</i>	-	-
<i>Bi- or Triamped HF/ Passive MF-HF</i>	12 Ohms	-
<i>Coverage (h° x v°)</i>	90x90	90x90
<i>Recommended Crossover</i>	1200 Hz	-
<hr/>		
DIMENSIONS (H X W X D)		
inches	53.00 x 29.25 x 11.75	53.00 x 29.25 x 11.75
millimeters	1346 x 743 x 298	1346 x 743 x 298
<hr/>		
WEIGHTS (Net/Shipping)		
pounds	103.0/115.0	103.0/115.0
kilograms	46.9/52.3	46.9/52.3



Sound is Half the Picture